

TAMPER-PROOF KEY RINGS®

THE INDUSTRY STANDARD AMONG SECURITY PROFESSIONALS.



No weak and bulky plastic joints with our Tamper Proof Key Rings.

Manufactured with the strictest tolerances to provide you with the ultimate in strength and durability, our popular Tamper-Proof Key Rings™ provide an added layer of protection for your most valuable assets – from keys and utility knives to medical equipment and cash tills. That's because these high-security, stainless steel rings cannot be opened without detection, making asset substitution impossible.

Unique ID



Each ring has its own unique serial number. This string of numbers and letters enables audits on both the rings and their keys. The permanent ID prevents someone from removing or substituting keys without detection.



Solid or Flexible

Tamper-Proof Key Rings™ are available in solid and flexible (braided) versions.



The Closing Tool

Closes any size ring in preparation for crimping.



The Crimping Tool

Squeezes the connection where the two ends meet creating a permanent seal.



The Cutting Tool

Used to cut open a Tamper-Proof Key Ring™ once it's been sealed.



Color Coded Control

The only plastic we use with our Tamper-Proof Key Rings™ is the color coded tags. They come in five different colors to help separate your keys by function, area and user.



Key Shield

Covering important key cuts prevents duplication.

Key Systems, Inc.

Ship: 7635 Glacier Hill,
Victor, NY 14564

Mail: PO Box G, Fishers, NY 14453

Sales & Customer Service

585.924.7830

800.888.3553

info@keystorage.com

Technical Support

585.924.7810

GFMS@keystorage.com

Play on your own.

Do this GFMS demonstration on your own web-enabled device. Call today for the TCP/IP address and password.

Tamper-Proof Key Rings (#5794991) and Vel-Key (#4137740/4072033) are registered trademarks. Registered trademarks are pending for Security Asset Managers, Global Facilities Management System, GFMS, Doorman (#7051563) and SWATBox.

Actual product may vary from images shown (i.e. doors of SAMs and Chit-Key Vaults have been removed for image clarity). Product specifications subject to change without notice.

Copyright 2007 Key Systems, Inc. All rights reserved.



Tamper-Proof Key Rings®

Solid Rings:

Material Stainless Steel
Ring Thickness 4mm

Diameter	Key Capacity*
1" (3cm)	14
1½" (4cm)	22
2" (5cm)	30
3" (7cm)	46
4" (9cm)	66

Flexible Rings:

Material Stranded Steel
Ring Thickness 2.6mm cable
 4mm seal

Diameter	Key Capacity*
1" (3cm)	14
1½" (4cm)	22
2" (5cm)	30
3" (7cm)	46
4" (9cm)	66

Tools:

- Item Closer [Black]
- Crimper [Yellow]
- Cutter [Red]

ACCESSORIES

Item	Color Options
Color Coded Control (Orders are in packages of 50)	Assorted Red Orange Yellow Green Blue
Key Shield	Blue Red

*Key Capacity is in terms of standard builders hardware